

ER220-3200	ER270-2850	ER280-3200	ER350-3300	ER500-2800	ER600-2800
Max 220^{kg} Capacity	Max 270^{kg} Capacity	Max 280^{kg} Capacity	Max 350^{kg} Capacity	Max 500^{kg} Capacity	Max 600^{kg} Capacity
					
Arm range 3200mm	Arm range 2850mm	Arm range 3200mm	Arm range 3300mm	Arm range 2800mm	Arm range 2800mm
Repeatability ±0.05mm	Repeatability ±0.06mm	Repeatability ±0.06mm	Repeatability ±0.1mm	Repeatability ±0.1mm	Repeatability ±0.1mm

kg Weight 1500 way to installation Floor IP54	kg Weight 1450 way to installation Floor IP54	kg Weight 1500 way to installation Floor IP54	kg Weight 3040 way to installation Floor IP54	kg Weight 3000 way to installation Floor IP54	kg Weight 3000 way to installation Floor IP54
1 ±180°	1 ±180°	1 ±180°	1 ±180°	1 ±180°	1 ±180°
2 -60° ~ +90°	2 -60° ~ +90°	2 -60° ~ +90°	2 -60° ~ +105°	2 -60° ~ +105°	2 -60° ~ +105°
3 -30° ~ +125°	3 -30° ~ +125°	3 -30° ~ +125°	3 -30° ~ +125°	3 -30° ~ +140°	3 -30° ~ +140°
4 ±200°	4 ±200°	4 ±200°	4 ±200°	4 ±200°	4 ±200°
5 ±125°	5 ±125°	5 ±125°	5 ±115°	5 ±115°	5 ±115°
6 ±360°	6 ±360°	6 ±360°	6 ±360°	6 ±360°	6 ±360°
1 110° /s	1 110° /s	1 110° /s	1 80° /s	1 80° /s	1 80° /s
2 100° /s	2 100° /s	2 100° /s	2 90° /s	2 90° /s	2 100° /s
3 100° /s	3 100° /s	3 100° /s	3 90° /s	3 90° /s	3 100° /s
4 170° /s	4 170° /s	4 170° /s	4 100° /s	4 100° /s	4 110° /s
5 145° /s	5 145° /s	5 145° /s	5 80° /s	5 80° /s	5 70° /s
6 200° /s	6 200° /s	6 200° /s	6 140° /s	6 140° /s	6 150° /s

ALL
MADE
BY ESTUN

ESTUN
ROBOTICS

ESTUN INDUSTRIAL ROBOTS

ER	6	B	730	MI	HI
ESTUN ROBOTIC	Max Payload		Arm range	MI: Mini robot with 6 joints	HI: High inertia
				SR: Scara robot	
				PL: Palletizing series	
				PR: Press series	
				F: Foundry series	
				BD: Bending series	
				DW: Downward series	
				AW: Arc welding	