

ER70B-2100-LI	ER100B-3500-DW	ER100B-3000	ER130B-3200	ER170B-2650	ER220B-2650
<b>Max</b> <b>70</b> kg Capacity	<b>Max</b> <b>100</b> kg Capacity	<b>Max</b> <b>100</b> kg Capacity	<b>Max</b> <b>130</b> kg Capacity	<b>Max</b> <b>170</b> kg Capacity	<b>Max</b> <b>220</b> kg Capacity
					
Arm range 2100mm	Arm range 3500mm	Arm range 3000mm	Arm range 3200mm	Arm range 2650mm	Arm range 2650mm
Repeatability ±0.05mm	Repeatability ±0.06mm	Repeatability ±0.06mm	Repeatability ±0.06mm	Repeatability ±0.06mm	Repeatability ±0.06mm

kg Weight	kg Weight	kg Weight	kg Weight	kg Weight	kg Weight
<b>530</b>	<b>1050</b>	<b>1053</b>	<b>1120</b>	<b>1090</b>	<b>1120</b>
way to installation Floor	way to installation Floor	way to installation Floor	way to installation Floor	way to installation Floor	way to installation Floor
<b>IP54</b>	<b>IP54</b>	<b>IP54</b>	<b>IP54</b>	<b>IP54</b>	<b>IP54</b>

1 ±180°	1 ±180°	1 ±180°	1 ±180°	1 ±180°	1 ±180°
2 -90° ~ +135°	2 -40° ~ +170°	2 -60° ~ +80°	2 -60° ~ +80°	2 -60° ~ +80°	2 -60° ~ +80°
3 -185° ~ +80°	3 -95° ~ +80°	3 -95° ~ +80°	3 -95° ~ +80°	3 -95° ~ +80°	3 -95° ~ +80°
4 ±200°	4 ±200°	4 ±200°	4 ±200°	4 ±200°	4 ±200°
5 ±130°	5 ±130°	5 ±130°	5 ±125°	5 ±125°	5 ±125°
6 ±360°	6 ±360°	6 ±360°	6 ±360°	6 ±360°	6 ±360°

1 189° /s	1 120° /s	1 120° /s	1 120° /s	1 120° /s	1 120° /s
2 134° /s	2 110° /s	2 110° /s	2 110° /s	2 110° /s	2 95° /s
3 186° /s	3 120° /s	3 120° /s	3 120° /s	3 120° /s	3 95° /s
4 255° /s	4 120° /s	4 140° /s	4 165° /s	4 200° /s	4 160° /s
5 254° /s	5 145° /s	5 187° /s	5 200° /s	5 215° /s	5 150° /s
6 366° /s	6 210° /s	6 285° /s	6 220° /s	6 300° /s	6 200° /s

**ALL  
MADE  
BY ESTUN**

**ESTUN**  
ROBOTICS



# ESTUN INDUSTRIAL ROBOTS

ER	6	B	730	MI	HI
ESTUN ROBOTIC	Max Payload		Arm range	MI: Mini robot with 6 joints	HI: High inertia
				SR: Scara robot	
				PL: Palletizing series	
				PR: Press series	
				F: Foundry series	
				BD: Bending series	
				DW: Downward series	
				AW: Arc welding	