

ER20-1780-F

Max
20 kg
Capacity



Arm range
1780mm

Repeatability
±0.03mm

ER30-1840-F

Max
30 kg
Capacity



Arm range
1840mm

Repeatability
±0.04mm

ER50B-2100-F

Max
50 kg
Capacity



Arm range
2100mm

Repeatability
±0.05mm



kg Weight
245

way to
installation
Floor / Ceiling

IP67

- 1 ±180°
- 2 -95° ~ +160°
- 3 -170° ~ +80°
- 4 ±180°
- 5 ±135°
- 6 ±360°

- 1 186° /s
- 2 186° /s
- 3 212° /s
- 4 480° /s
- 5 350° /s
- 6 585° /s

kg Weight
255

way to
installation
Floor

IP67

- 1 ±180°
- 2 -95° ~ +160°
- 3 -170° ~ +80°
- 4 ±180°
- 5 ±130°
- 6 ±360°

- 1 186° /s
- 2 186° /s
- 3 212° /s
- 4 480° /s
- 5 310° /s
- 6 407° /s

kg Weight
530

way to
installation
Floor

IP67

- 1 ±180°
- 2 -90° ~ +135°
- 3 -185° ~ +80°
- 4 ±200°
- 5 ±130°
- 6 ±360°

- 1 172° /s
- 2 119° /s
- 3 186° /s
- 4 255° /s
- 5 254° /s
- 6 366° /s

**ALL
MADE
BY ESTUN**

ESTUN
ROBOTICS

ESTUN INDUSTRIAL ROBOTS

ER

ESTUN ROBOTIC

6

Max Payload

B

730

Arm range

MI

MI: Mini robot with 6 joints

SR: Scara robot

PL: Palletizing series

PR: Press series

F: Foundry series

BD: Bending series

DW: Downward series

AW: Arc welding

HI

HI: High inertia