

ER45-2200-BD

Max
45 kg
Capacity



Arm range
2200mm

Repeatability
±0.08mm

ER80B-2565-BD

Max
80 kg
Capacity



Arm range
2565mm

Repeatability
±0.04mm

ER130-2865-BD

Max
130 kg
Capacity



Arm range
2865mm

Repeatability
±0.04mm

kg Weight
520

way to
installation
Floor

IP54

kg Weight
730

way to
installation
Floor

IP54

kg Weight
950

way to
installation
Floor

IP54

- 1 ±190°
- 2 -70° ~ +110°
- 3 -95° ~ +62°
- 4 ±200°
- 5 ±130°
- 6 ±360°

- 1 172° /s
- 2 119° /s
- 3 193° /s
- 4 296° /s
- 5 247° /s
- 6 355° /s

- 1 ±185°
- 2 -67° ~ +150°
- 3 -190° ~ +66°
- 4 ±200°
- 5 ±130°
- 6 ±360°

- 1 114° /s
- 2 108° /s
- 3 137° /s
- 4 255° /s
- 5 197° /s
- 6 285° /s

- 1 ±180°
- 2 -70° ~ +90°
- 3 -200° ~ +68°
- 4 ±200°
- 5 ±125°
- 6 ±360°

- 1 112° /s
- 2 106° /s
- 3 106° /s
- 4 180° /s
- 5 175° /s
- 6 188° /s

**ALL
MADE
BY ESTUN**

ESTUN
ROBOTICS

ESTUN INDUSTRIAL ROBOTS

ER	6	B	730	MI	HI
ESTUN ROBOTIC	Max Payload		Arm range	MI: Mini robot with 6 joints	HI: High inertia
				SR: Scara robot	
				PL: Palletizing series	
				PR: Press series	
				F: Foundry series	
				BD: Bending series	
				DW: Downward series	
				AW: Arc welding	