

ER7-910-MI	ER8-720-MI	ER10-900-MI/Hi
<div>Max 7 kg Capacity</div>	<div>Max 8 kg Capacity</div>	<div>Max 10 kg Capacity</div>
		
Arm range 917mm	Arm range 727mm	Arm range 900mm
Repeatability ±0.03mm	Repeatability ±0.02mm	Repeatability ±0.03mm
  	  	  
<div>kg Weight 46</div> <div> way to installation Floor / Ceiling</div> <div>IP67</div>	<div>kg Weight 48</div> <div> way to installation Floor / Ceiling</div> <div>IP67</div>	<div>kg Weight 75</div> <div> way to installation Floor / Ceiling</div> <div>IP54</div>
<div>1 ±170°</div> <div>2 -80° ~ +135°</div> <div>3 -190° ~ +65°</div> <div>4 ±190°</div> <div>5 ±120°</div> <div>6 ±360°</div>	<div>1 ±170°</div> <div>2 -80° ~ +135°</div> <div>3 -190° ~ +65°</div> <div>4 ±190°</div> <div>5 ±120°</div> <div>6 ±360°</div>	<div>1 ±176°</div> <div>2 ±140°</div> <div>3 -200° ~ +70°</div> <div>4 ±173°</div> <div>5 ±130°</div> <div>6 ±360°</div>
<div>1 420° /s</div> <div>2 380° /s</div> <div>3 450° /s</div> <div>4 550° /s</div> <div>5 500° /s</div> <div>6 850° /s</div>	<div>1 420° /s</div> <div>2 380° /s</div> <div>3 450° /s</div> <div>4 550° /s</div> <div>5 500° /s</div> <div>6 850° /s</div>	<div>1 350° /s</div> <div>2 350° /s</div> <div>3 355° /s</div> <div>4 480° /s</div> <div>5 400° /s</div> <div>6 500° /s</div>

ALL
MADE
BY ESTUN

ESTUN
ROBOTICS

ESTUN INDUSTRIAL ROBOTS

ER	6	B	730	MI	HI
ESTUN ROBOTIC	Max Payload		Arm range	MI: Mini robot with 6 joints SR: Scara robot PL: Palletizing series PR: Press series F: Foundry series BD: Bending series DW: Downward series AW: Arc welding	HI: High inertia